

Product
Catalog

The Best Quality Fire Hydrant Equipment



Hydrant Box



Remark	Indoor Hydrant Box			Outdoor Hydrant Box
Type	A1	A2	B	C
Size	66 x 52 x 15 cm	100 x 80 x 18 cm	125 x 75 x 18 cm	95 x 66 x 20 cm
Plate	1,2 mm MILD STEEL			
Production Process	DUST REMOVER, PHOSPATING & ZINCROMATE PRIMER			
Finishing	TOP COAT POWDER COATING RED SIGNAL			

Option: All type of boxes can be used glass door + lock

			
Hose Rack	Hydrant Valve	Hose Nozzle	Siamese Connection
Size : 1.5" & 2.5"	Model : Machino & VDH	Model : Machino	Model : Machino & VDH
Material : Alumunium A380	Size : 1.5" & 2.5"	Size : 1.5" & 2" & 2.5"	Type : S7 & S11
Finishing : Chrome Plated	Material : Brass C3604	Material : Alumunium A6061	Size : 4" x 2.5" x 2.5"
Weight : 1.5" = 0.701 kgs	Finishing : Chrome Plated	Finishing : Anodize	Material : Brass
2.5" = 0.784 kgs	Weight : 1.5" = 0.92 kgs	Weight : 1.5" = 0.364 kgs	Finishing : Chrome Plated
Lenght : 1.5" = 52 cm	2.5" = 3.00 kgs	2.5" = 1.065 kgs	Weight : 8800gr
2.5" = 54 cm	Lenght : 1.5" = 145 mm	Lenght : 1.5" = 457 mm	
	2.5" = 190 mm	2" = 590 mm	
		2.5" = 730 mm	

Fire Hose

TPU fire hose is a hose using polyurethane canvas material, which is resistant to extreme weather. How to check whether or not the original hose can be seen in the 3 color lines made of knitted yarn, not paint color.

Fire Hose TPU 1,5"

Standard coupling uses Machino Coupling (MCH) type. Size of 1.5" can be used for indoor hydrant installation. Diameter smaller than outdoor mounting.



Fire Hose TPU 2,5"

Standard coupling uses a Machino Coupling (MCH) type or can use VDH. Size 2.5" can be used for outdoor hydrant installations.



TECHNICAL DATA

- Testing Pressure : 16 bar (20 bar 350 psi)
- Heat Resistance : + 70° C
- Cold Resistance : - 40° C
- Maximum Lenght : 100 ft (30meter) / roll

SPECIAL FEATURES

- Made up of 100% polyester staple and polyester filaments.
- It resists high pressure. Lining is used the imported TPU with Germany first technics
- Special adhesion is used between the jacket and the lining
- It has good resistance in cold weather
- Character: light, resisting high pressure, soft resisting cold and long service life

Size	Material	Working Pressure	Coupling Model	Heat Resistance	Cold Resistance	Length	Weight
1,5"	Polyester	16 bar	Machino	70°C	-40°C	20m & 30m	6.1 kg
2"	Polyester	16 bar	Machino	70°C	-40°C	20m & 30m	8 kg
2,5"	Polyester	16 bar	Machino & VDH	70°C	-40°C	20m & 30m	10.7 kg

Hydrant Pillar

Pillar Hydrant serves as a blackout water controller installed in the outdoor / outdoor area. Fire hose and nozzle are stored in the outdoor hydrant box type C.

Specification

- Model Type** : Two ways & one way
: H-13AP (One way)
: H-14AP (Two ways)
- Connection Size** : Flange JIS
: 3" x 2.5" (One way)
: 4" x 2,5" x 2,5" (Two ways)



Hydrant Pillar Two Ways



Hydrant Pillar One Way



HOOSEKI
BUILDING



CV. SUKSES MANDIRI

HOOSEKI
BUILDING